### **ES7412 Dealer Specifications**



## An outstanding high print quality, fast and reliable LED color printer for mid to enterprise network environments

The ES7412, a highly reliable HD color printer utilizing OKI LED technology to produce vibrant and colorful graphics for mid to large size workgroups in fast-paced office environments.

#### **Key features**

- HD Color LED printing technology with multi-level output quality
- Low running costs
- Flexible media capabilities including up to 52" banners and a variety of heavy stock media
- Security features protecting your documents, your devices and your network
- Google Cloud Print 2.0 ready enabling printing on the move and direct printing using Local Mode



BUILDINGWORX ANNUAL REPORT

DESIGN LINE

#### **Simplicity**

- Easy to set-up and get started.
- As new features become available, update the printer via the OKI portal

#### **Security Features**

- Keep documents confidential with Private Print<sup>7</sup> and optional Card Release while selecting which jobs to print
- Internet Protocol Security (IPSec) compliance, ensuring that documents are safely sent and received



# Sign up NOW! Science Symposium Thomas Barnes Center for Bilogy



#### Advanced connectivity

- Print direct using front facing USB port
- Wireless Direct offers safe simultaneous connection of wired and wireless networking
- Gigabit Ethernet enables fast transfer of large color files across the network
- Google Cloud Print 2.0 ready
- Optional Wireless LAN Module available

#### Cost and energy saving

- LED technology means high reliability, less down time, and longer life
- ENERGY STAR® Compliant
- Enable Toner Save Mode to reduce costs
- Duplex printing reduces paper usage
- Low power consumption with Deep Sleep mode and Auto-Off mode
- Create cost efficiencies printing outstanding high quality marketing materials in-house with LED technology and media flexibility

A4/Letter	✓
Color/Mono	✓
Networked/Duplex	✓
1 – 45 users	<b>√</b>

#### **ES7412 Specifications**

Up to 35ppm Color/ 37 ppm Mono <sup>1</sup>			
9 seconds Color, 8 seconds Mono <sup>1</sup>			
533 MHz			
up to 1200 x 600 dpi			
Maximum up to 100,000 pgs/month			
Recommended up to 6,000 pgs/month			
Mono Graphic Panel			
256 MB Standard; 768 MB Max; Optional SDHC 16GB			
Interface and Software			
USB 2.0 Device, 10 Base-T/100 Base-TX/1000 Base-T Ethernet; Wireless (Option) IEEE802.11a/b/g/n			
PCL6 (XL3.0) and PCL5c, Postscript 3 (emulation), IBM-PPR, EPSON-FX, XPS, PDF (V1.7)			
TCP/IPv4&v6, NetBIOS over TCP, DHCP, DHCPv6, BOOTP, HTTP, HTTPS, DNS, DDNS, WINS, UPNP, Bonjour, SMTP, SMTPS, POP3, SNMPv1&v3, SNTP, IPP, IPPS, WSD Print, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, FTPS, IPSec, Google Cloud Print 2.0, Wireless IEEE802.11a/b/g/n, WEP, WPA(Personal, Enterprise), WPA2(Personal, Enterprise)			
Vista (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows 8 (32-bit & 64-bit) / Server 2012 (64-bit) / Windows 8.1 (32-bit & 64-bit) / Server 2012 R2 (64-bit) / Windows 10 (32-bit & 64-bit); Linux PPD; Mac OS X 10.8.5 to 10.11			
Color Correct, OKI LPR <sup>5</sup> , Color Swatch Utility <sup>5</sup> , smart PrintSuperVision <sup>5</sup> , Print Job Accounting Client, Web Driver Installer <sup>5</sup> , Network Card Setup <sup>6</sup> , Configuration Tool <sup>5</sup> , PS Gamma Adjuster, PDF Direct Print <sup>5</sup> , Firmware Update Tool, Profile Assistant <sup>6</sup>			
Scalable: 87 PCL fonts, 80 PostScript fonts			
4 PCL fonts (Line Printer, OCR-A/B, USPS ZIP Barcode)			
10 types of one dimension with 26 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET; 2 types of two dimensions: PDF417, JIS-X0510,QR code Model 2			
630 sheets of 80gsm Standard (530-sheet Main Tray + 100-sheet Multi-Purpose Tray); 1,690 sheets Max (with Optional 530-sheet 2nd & 3rd Trays)			
630 sheets of 80gsm Standard (530-sheet Main Tray + 100-sheet Multi-Purpose Tray); 1,690 sheets Max (with			
630 sheets of 80gsm Standard (530-sheet Main Tray + 100-sheet Multi-Purpose Tray); 1,690 sheets Max (with Optional 530-sheet 2nd & 3rd Trays)  Main Tray/Duplex/Optional Tray from 5.8" x 8.3" to 8.5" x 14";			

Enne	DO N	 

Size (WxDxH)	17.1" x 23.8" x 15.3" (435mm x 604mm x 389mm)
Weight	Approx. 68.3 lbs (31 kg)
Acoustic Noise	Operating 54dBA or less; Standby 37dBA; Power Save Inaudible
Power Consumption	Typical: 600W; Peak: 1300W; Idle: 100W; Power Save: <15W; Deep Sleep: <0.9W; Auto-Off: <0.5W
ENERGY STAR 2.0 Compliance	Yes

#### WARRANTY

Printer	3-Year On Site <sup>2</sup>
LED Printheads	5-Year limited warranty

#### H/W

**ES7412, 120V** 62447901

#### CONSUMABLES (ORDER NUMBERS)

Toner cartridges <sup>3</sup> (10,000 pages)	Cyan: 46507607; Magenta: 46507606; Yellow: 46507605
Toner cartridge <sup>3</sup> (10,700 pages)	Black: 46507608
	Cyan: 46507407; Magenta: 46507406; Yellow: 46507405; Black: 46507408

#### **OPTIONS (ORDER NUMBERS)**

OFTIONS (ORDER NUMBERS)	
530-sheet 2nd/ 3rd Paper Tray	44274501
256 MB RAM	70061801
512 MB RAM	70061901
16 GB SDHC Memory Card	70061701
IEEE802.11a/b/g/n Wireless	45830201









- $^{\scriptscriptstyle 1}$  Published performance results based on laboratory testing. Individual results may apply.
- <sup>2</sup> Available in the U.S. and Canada only.
- <sup>3</sup> Average A4 continuous print page yield based upon 5% coverage. Individual results may vary. Printer shipped with toner for 9.9K (CMY) and 9.4K (K) A4 pages.
- $^{\mbox{\tiny 4}}$  Estimated average life, based on 3 pages per job.

Duplex (2-sided) Printing | Standard

- 5 Windows only.
- 6 Mac OSX only.
- $^{\scriptscriptstyle 7}\,\text{SDHC}$  memory card required.

 $Specifications\ are\ subject\ to\ change\ without\ notice.$ 

© 2016 Oki Data Americas, Inc. OKI Reg. T.M., M.D., Oki Electric Industry Co., Ltd. Adobe Reg. T.M., PostScript 3 T.M., Adobe Systems, Inc. PCL Reg. T.M., Hewlett-Packard Co. Windows, Windows Vista Reg. T.M., Microsoft Corp. XPS Reg. T.M., Dell, Inc. Mac Reg T.M., Apple Inc. Harlequin Reg. T.M., MultiRIP, DirectPrint, T.M., Global Graphics Software Ltd. EFI Reg. T.M., Electronics for Imaging, Inc. ENERGY STAR Reg. T.M., US EPA. Google Cloud Print is a trademark of Google Inc.

OKI DATA AMERICAS, INC.

US

2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 800.OKI.DATA (800.654.3282)
FAX: 856.222.5320

CANADA

5800 HURONTARIO ST. SUITE 1020MISSISSAUGA, ONTARIO L5R 4B9 TEL: 905.608.5000 FAX: 905.608.5040

WWW.OKIDATA.COM



Printed in the USA MS16186-0317