

# intelliFAX-5750e

NETWORK-READY  
BUSINESS CLASS FAX  
**LASER**

## FEATURING

- Super G3, 33.6K bps High Speed Fax Modem
- Dual 250-Sheet Paper Trays standard, for a total paper capacity of 500 sheets
- 8MB Memory stores up to 600 Pages\* for Out-of-Paper Reception and Memory Transmission
- Up to 15ppm Laser Engine for printing of faxes and copies
- Up to 50-Page Auto Document Feeder



**8MB**  
MEMORY with  
BROADCASTING

**SUPER G3**  
33.6K bps High-Speed  
FAX

500  
SHEET  
PAPER CAPACITY



At your side.™

# brother®

# intelliFAX-5750e

NETWORK-READY  
BUSINESS CLASS FAX

LASER



## Featuring...

- Super G3, 33.6K bps High Speed Fax Modem
- Dual 250-Sheet Paper Trays standard, for a total paper capacity of 500 sheets
- 8MB Memory stores up to 600 Pages\* for Out-of-Paper Reception and Memory Transmission
- Up to 15ppm Laser Engine for printing of faxes and copies
- Up to 50-Page Auto Document Feeder
- 10/100 BaseTX Ethernet Network Print/Fax Server standard
- Quickly scan faxes as fast as 2 secs./page\*
- 232 Station Auto Dialing (32 One-Touch Keys, plus up to 200 speed dial locations)
- High Yield Toner Cartridges deliver low printing costs per page†
- Fax Broadcasting to up to 282 Locations
- Multi-Copying up to 99 copies, plus Sorting
- Copy Reduction and Enlargement, 50%-200%

**8MB**  
MEMORY with  
BROADCASTING

**DUAL**  
Scan a fax into memory while  
another is being sent or received.  
**ACCESS**

UP TO  
**6,000** PAGE  
YIELD  
TONER


**500** SHEET  
PAPER CAPACITY

## Other Standard Features

- Dual Access capability lets you scan faxes into memory while the unit is busy sending or receiving
- 4-Day Battery Back-up for Fax Memory
- Fax Security with password controlled access
- Auto Fax/Tel Switching for receiving fax and voice calls on a single phone line
- Fax Forwarding, Paging and Remote Fax Retrieval
- Telephone Handset
- Caller ID and Distinctive Ring Detection ready‡
- Built-in Parallel and USB interfaces for future printing needs (cables not included)

## BUILT-IN NETWORK PRINT/FAX SERVER

Provides scanning and internet faxing via E-mail\*, plus network printing for small workgroups\*\*.



◆ SMTP/POP3 E-mail server support required  
◆◆ Support For:

- Windows® 2000 Professional TCP/IP
- Windows® XP TCP/IP
- Windows NT® 4.0 TCP/IP
- Windows® 95/98/98SE/Me TCP/IP Peer-To-Peer
- UNIX TCP/IP
- AppleTalk®
- Novell Netware®

\* Based on Brother #1 Chart with JBIG coding and standard resolution.

† Based on 5% page coverage using optional TN460 Toner Cartridge (cartridge requires additional purchase).

‡ Requires additional purchase.

▲ Check with local phone company for availability of and charges for these services.

All trademarks and registered trademarks referenced herein are the property of their respective companies.

© 2002 BROTHER INTERNATIONAL CORPORATION, 100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911  
For more information please call the Brother Fax-Back System at 1-800-521-2846 (USA ONLY)  
or visit our web site at [www.brother.com](http://www.brother.com).

All specifications are subject to change without notice. Printed in USA. CATFX5750e

## PRODUCT SPECIFICATIONS

Approved:	UL and FCC
Unit Dimensions:	17.4" x 17.1" x 17.0"
Unit Weight:	31.1 lbs.
Carton Dimensions:	22.8" x 21.1" x 27"
Carton Weight:	50.7 lbs.
UPC Code:	0 12502 60284 2
Compatibility:	ITU-T Group 3
Coding Method:	MH/MR/MMR/JBIG
Modulation:	33600/31200/28800/26400/24000/ 21600/19200/16800/14400/ 12000/9600/7200/4800/2400 bps
Transmission Time:	As fast as 2 seconds per page (Brother #1 Chart, JBIG)
Printing Method:	Electrophotography
Copy Speed:	Up to 15 copies per minute
Document Input Width:	5.8" to 8.5"
Recording Paper Size:	8.5" x 11" / 8.5" x 14"
Scanning/Recording Width:	8.2"
Resolution Standard:	203 x 98 lines/inch
Fine Mode:	203 x 196 lines/inch
Superfine:	203 x 392 lines/inch
Display:	LCD, 2 lines by 16 characters
Gray Scale:	64 shades
Interfaces (Standard):	USB and High-Speed, Bi-Directional, Parallel Centronics (cables not included)
Dialing System:	Selectable Pulse/Tone
Speaker Type:	Monitor
Communication Source:	Public Switched Telephone Network
Connection Requirements:	USOC RJ11C Modular Jack (or equivalent)
Power Supply:	120V, 50/60 Hz
Power Consumption:	Average Operating (Copying): 350W Standby: 70W or less Sleep Mode: 10W or less
Noise Level:	53 dBA Printing 30 dBA Standby
Operating Environment:	50° to 90.5° F
Standard Toner Cartridge:	Up to 3,000 pages @ 5% coverage

## OPTIONAL ACCESSORIES†

TN430:	Standard Yield Toner Cartridge (Up to 3,000 pages @ 5% coverage)
TN460:	High Yield Toner Cartridge (Up to 6,000 pages @ 5% coverage)
DR400:	Replacement Drum Unit

use only  
**GENUINE**  
brother  
supplies

At your side.™  
**brother**®

[www.brother.com](http://www.brother.com)