



BRIDGE THE GAP
BETWEEN PAPER AND DIGITAL
BUSINESS-CLASS
DOCUMENT SOLUTIONS

MFX-iNTELLIGENT Series



## **CUSTOMER BENEFITS**



## Intuitive operability

Operate the Muratec MFX like a smartphone or tablet with fully customized user interface



#### Mobile connectivity

Print anytime from anywhere with Muratec's innovative mobile technologies



#### Security

Secure network integration, data encryption, and advanced user authentication



#### Application ecosystem

Enhanced efficiency thanks to Muratec's extensive applications portfolio



### **Productivity**

Reliability, high-speed scanning and printing, combined with powerful finishing functions



#### Sustainability


Numerous eco features reduce energy consumption and costs

## **OPTIONS**



**IP fax (T.38 fax)** LK-117\*










This option can only be installed with the respective option above it



\* May not be available at time of launch.

# 5 MEDIA OUTPUT Job separator

nner finisher Attachment kit

**Punch kit for FS-533** PK-519

Staple finisher FS-539 Relay unit Booklet finisher FS-539SD

Punch kit for FS-539/SD

Staple finisher FS-540 Relay unit Booklet finisher FS-540SD

Punch kit for FS-540/SD PK-526

Job separator for FS-540/SD JS-602 Z-fold unit for FS-540/SD

## FINISHING FUNCTIONALITIES



stapling







punching



Duplex



mixplex/ mixmedia



Half-fold insertion





Tri-fold





sorting



Z-fold





printing stapling (offline)

# **DESCRIPTION**

						π		

LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document	Generates various file formats including
file conversion	DOCX, XLSX and PDF/A
LK-111 ThinPrint client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender* antivirus provides real time scanning of all incoming and
 LK-117 IP fax (T.38 fax)*	outgoing data
LN-11/ IP IdX (1.30 IdX)"	Fax over IP networks (T.38), requires fax kit

## CONNECTIVITY

FK-514 Fax board	Super G3 fax, digital fax functionality			
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode			
EK-608 USB I/F kit	USB keyboard connection			
EK-609 USB I/F kit	USB keyboard connection, Bluetooth			
IC-420 Fiery controller	Professional color print controller			
VI-516 Interface kit for IC-420	Fiery controller interface card			
UK-115 Mount kit	Fiery controller mount kit			
AU-102 Biometric authentication	Finger vein scanner			
AU-205H ID card reader	Supports various ID card technologies			
MK-735 Mount kit	Installation kit for ID card reader			

## **OTHERS**

WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For numeric entry instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard
External keyboard	Keyboard for alpha numeric data entry

## **MEDIA INPUT**

PC-116 1x Universal tray	500 sheets / 5.5" x 8.5" — 11" x 17" / 52—256 g/m²
PC-216 2x Universal tray	2x 500 sheets / 5.5" x 8.5" — 11" x 17" / 52—256 g/m <sup>2</sup>
PC-416 Large capacity tray	2,500 sheets / 8.5" x 11" / 52—256 g/m²
PC-417 Large capacity tray	1,500 + 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m²
LU-302 Large capacity tray	3,000 sheets / 8.5" x 11" / 52—256 g/m <sup>2</sup>
LU-207 Large capacity tray	2,500 sheets / 8.5" x 11" — 12" x 18" / 52—256 g/m <sup>2</sup>
MK-730 Banner tray	Multipage banner feeding
DK-516 Copier desk	Provides storage space for print media and other materials

## **MEDIA OUTPUT**

Output tray used instead of finisher
Separation of fax output; etc.
50-sheet stapling, 500 sheets max. output
For FS-533 installation
2/4 hole punching, auto switching
50-sheet stapling / 3,200 sheets max. output
50-sheet stapling / 20-sheet booklet finisher / 2,200 sheets max. output
2/3 hole punching, auto switching
100-sheet stapling / 3,200 sheets max. output
100-sheet stapling / 20-sheet booklet finisher / 2,700 sheets max. output
2/3 hole punching, auto switching
For FS-539/SD or FS-540/SD installation
Separation of fax output, etc.
Cover insertion, post finishing
Z-fold for 11" x 17" prints

# **TECHNICAL SPECIFICATIONS**

## **SYSTEM SPECIFICATIONS**

System speed 8.5" x11"	Up to 55/55 ppm (mono/color)
System speed 11" x 17"	Up to 27/27 ppm (mono/color)
Auto duplex speed 8.5" x 11"	Up to 55/55 ppm (mono/color)
1st page out time 8.5" x 11"	3.3/4.3 sec. (mono/color)
Warm-up time	Approx. 14/16 sec. (mono/color) <sup>1</sup>
lmaging technology	Laser
Toner technology	Simitri® HD polymerized toner
Panel size/resolution	10.1" / 1,024 x 600
System memory	8 GB (standard/max.)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet, USB 2.0, Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6) / SMB / LPD / IPP / SNMP / HTTP(S) / Bonjour
Automatic document feeder	Up to 300 originals / 5.5" x 8.5" — 11" x 17" / 35—210 g/m² / Dualscan ADF
ADF double feed detection	Standard
Printable paper size	3.5" x 5.5" — 12" x 18" / customized paper sizes / banner paper max. 47.2" x 11.7"
Printable paper weight	52–300 g/m <sup>2</sup>
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max.)
Paper tray input (standard)	1 x 500 / 3.5" x 5.8" — 11" x 17" / custom sizes / 52—256 g/m² 1 x 500 / 5.5" x 8.5" — 12" x 18" / custom sizes / 52—256 g/m²
Paper tray input (optional)	1 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m <sup>2</sup> 2 x 500 / 5.5" x 8.5" – 11" x 17"/ 52–256 g/m <sup>2</sup> 1 x 2,500 / 8.5" x 11" /52–256 g/m <sup>2</sup> 1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m <sup>2</sup>

Large capacity tray (optional)	1 x 3,000 / 8.5" x 11" / 52–256 g/m <sup>2</sup>
	1 x 2,500/ 8.5" x 11" – 12" x 18" / custom sizes / 52–256 g/m²
Manual bypass	150 sheets / 3.5" x 5.5" — 12" x 18" / custom sizes / banner / 60—300 g/m²
Finishing modes (optional)	Offset, Group, Sort, Staple, Staple (offline), Punch, Half-fold, Letter-fold, Booklet, Post insertion, Z-fold
Automatic duplexing	4.1" x 5.5" — 12" x 18" / 52—256 g/m²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max.)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets
	(up to 300 g/m²)
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets, unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets $+$ 1 cover sheet (up to 300 q/m <sup>2</sup> )
Booklet output capacity	Max. 35 booklets, unlimited (without tray)
Duty cycle (monthly)	Max. <sup>2</sup> 200,000 pages
Toner lifetime	Black up to 28,000 pages CMY up to 28,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer) CMY up to 165,000/1,000,000 pages (drum/developer)
Power consumption	110—120 V / 60 Hz, Less than 1.6 kW
System dimension (W x D x H)	24.2" x 27.1" x 37.8" (without options)
System weight	Approx. 220 lb (without options)

## **PRINTER SPECIFICATIONS**

Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
Page description language	PCL 6 (XL3.0), PCL 5c, PostScript 3 (CPSI 3016), XPS
Operating systems	Windows 7 (32/64), Windows 8.1 (32/64),
	Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008
	R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016,
	Windows Server 2019, Macintosh OS X 10.10 or later, Unix, Linux, Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS), Konica Minolta Print Service (Android),
	Konica Minolta Mobile Print (iOS/Android)
	Optional: Google Cloud Print

#### PRINTER SPECIFICATIONS (OPTIONAL)

I MINIER SI ECH ICATIONS (OF HOMAE)				
Print controller	Embedded Fiery IC-420			
Controller CPU	AMD GX-424CC @ 2.4 GHz			
Memory/HDD	4 GB / 500 GB			
Page description language	Adobe PostScript 3 (CPSI 3020), PCL 6, PCL 5c			
Operating systems	Windows 7 (32/64), Windows 8.1 (32/64), Windows 10 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Macintosh OS X 10.10 or later, Linux			

#### CCANNED CDECIEICATIONS

SCANNER SPECIFICAL	IUNO
Scan speed	Up to 140/140 ipm in simplex (mono/color)
	Up to 280/280 ipm in duplex (mono/color)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me), Scan-to-SMB (Scan-to-Home), Scan-to-FTP,
	Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Scan-to-URL,
	TWAIN scan
File formats	JPEG, TIFF, PDF, Compact PDF, Encrypted PDF, XPS,
	Compact XPS, PPTX
	Optional: Searchable PDF, PDF/A 1a and 1b, Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups, LDAP support

## **COPIER SPECIFICATIONS**

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	Max. 11" x 17"
Magnification	25—400% in 0.1% stens. Auto zoom

#### **FAX SPECIFICATIONS**

Fax standard	Super G3 (optional)
Fax transmission	Analog, i-Fax, Color i-Fax, IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH, MR, MMR, JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

## **USER BOX SPECIFICATIONS**

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public, Personal (with password or authentication), Group (with authentication)
Type of system boxes	Secure print, Encrypted PDF print, Fax receipt, Fax polling

## **SYSTEM FEATURES**

Security	ISO 15408 HCD-PP Common Criteria (in evaluation), IP filtering and port blocking, SSL3 and TLS1.0/1.1/1.2 network communication, IPsec support, IEEE 802.1x support, User authentication, Authentication log, Secure print, Kerberos, Hard drive data encryption (AES 256), Confidential fax, Print user data encryption Optional: Antivirus scanning (Bitdefender®), Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts, Active Directory support (user name + password + e-mail + smb folder), User function access definition, Authentication by mobile device (Android) Optional: Biometric authentication (finger vein scanner), ID card authentication (ID card reader), Authentication by mobile device (iOS)
Software	Net Care Device Manager, Data Administrator, Box Operator, Web Connection, Print Status Notifier, Driver Packaging Utility, Log Management Utility

<sup>1</sup> Warm-up time may vary depending on the operating environment and usage.

<sup>2</sup>Maximum monthly copy/print volume supported under standard vendor-supplied service defines the upper end of expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on a continual basis.

- All specifications refer to 8.5" x 11" paper of 80 g/m² weight.
- The support and availability of the listed specifications and functionalities vary depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- $\ \ \text{Specifications and accessories are based on the information available at the time of printing and are subject to change without}$
- Muratec does not warrant that any specifications mentioned will be error-free.



















For complete information on Muratec products and solutions,

please contact: 469.429.3300 or visit www.muratec.com





14800 Landmark Blvd., Suite 720, Dallas, TX 75254

www.muratec.com