ML600 Series



The ML600 Series from OKI: high-volume versatility in forms and correspondence.

Whether your output is continuous multi-part forms or fine business correspondence—you'll find your solution in the Dual 9-pin ML620/ML621 or the 24-pin ML690/ML691 dot matrix printers.

They handle the printing needs of the most demanding environments—including point-of-sale, automation and utility applications such as wholesale or retail sales counters, financial departments, manufacturing and warehousing.

Yet they also produce letter-quality type and high-resolution graphics for the office and executive suite.

Unequaled performance – ML600 Series printers have features that give them a strong edge over the competition:

- Print speeds of up to 700 cps1
- An MTBF rating of 25,000 hours
- Ribbon life of up to 13 million characters²

And they offer other features that will improve your working conditions, including:

- A convenient front paper path (tractor feed and friction feed)
- Printing on forms up to 7 parts3
- Versatile connectivity and paper handling

Fast, with finesse – ML600 Series printers run the gamut of paper types and envelopes at lightning speed. Their rugged printheads have a 400 million-character average life expectancy, with powerful samarium magnets and stored-energy pins that deliver precise, sharp characters through to the last page of a 7-part form³.

Sturdy and sophisticated – Field-proven reliability is just one reason OKI MICROLINE® printers are the most widely-used impact printers in North America4. The rugged, reliable OKI ML600 Series printers are sure to win you over, too!

Step up to superior performance – OKI provides products that increase performance without increasing the budget.

You can expect more from ML600 Series printers: faster speeds... better performance... greater reliability.

Highlights:

- Dual 9-pin and 24-pin dot matrix printing
- Best-in-class reliability: 25,000-hour MTBF
- Convenient front paper feed
- Fastest-in-class print speeds: up to 700 cps1
- Up to 13 million-character ribbon life²
- USB and Parallel connectivity standard
- Crisp, clear printing on letterhead or up to 7-part forms³
- 128 KB receive buffer/memory
- 400-million character printhead life
- Options include internal Ethernet and Serial connectivity; front/back tractors; top pull tractor; cut sheet feeder; roll paper stand⁶
- 3-year standard warranty with extensions⁵
- Live, toll-free technical support⁵
 - ¹ ML620/ML621 SuperSpeed Draft; ML690/ML691 up to 480 cps.
- $^2\,\text{ML}621/\text{ML}691;\,\text{ML}620/\text{ML}690$ at 8 million-character life.
- ³ 7 sheets max, depending on paper path and tractor used.
- ⁴ IDC Quarterly Tracker, 2019.
- ⁵ Available in the U.S. and Canada only.
- ⁶ Roll paper stand for ML620/ML690 only.





ML620/ML690 Narrow-body

ML621/ML691 Wide-body

ML600 Series

Specifications

Technology, Speed and Print Characteristics

 Print Method: Serial Impact Dot Matrix ML620/ML621 – Dual 9-pin (0.3 mm diameter)
 ML690/ML691 – 24-pin (0.2 mm diameter)

Print Speed¹ (cps):

NLQ & LQ	Draft	HS Draft	SS Draft
ML620/ML621 113 (NLQ)	450	600	700
ML690/ML691	360	480	N/A

Graphics Resolution (max):

ML620/ML621 – 288 (H) x 72 (V) dpi OKI® MICROLINE®; 240 (H) x 72 (V) dpi Epson®/IBM®

ML690/ML691 - 360 (H) x 360 (V) dpi Epson/IBM

 Feed Rate: ML620/ML621 – 5.25 ips; ML690/691 – 5.5 ips

Emulations, Interface and Memory

Emulation:

ML620/ML621 – Epson® FX(ESC/P), IBM® PPDS, OKI MICROLINE

ML690/ML691 – Epson LQ (ESC/P2), IBM PPDS, IBM AGM

• Interface:

Standard – IEEE Bi-directional Parallel, USB 2.0; Optional – Ethernet® via OkiLAN® 7130E 10/100 Base-T Internal Print Server, RS-232C Serial Receive Buffer/Memory: 128 KB

Compatibility

 Operating Systems: Windows®10, Windows 8.1, Windows 8, Windows 7, Server 2019, Server 2016, Server 2012/R2, Server 2008/R2, Server 2003, Vista, XP

Fonts/Characters

Scalable:

ML620/ML621 – Courier and Gothic 22-216 pt.
ML690/ML691 – Courier, Roman and Swiss 8-64 pt.

Bar Codes: 11

Paper Handling

- Paper Input: Single/Multi-part, Continuous forms, Cut sheet, Roll paper², Envelopes, Card stock, Labels
- Number of Copies:

Original + up to 6 copies max³

- Thickness (Max): Front/Back push 0.014" (0.36mm);
 Front/Back pull, Front/Back push-pull 0.017" (0.44 mm);
 Top pull 0.019" (0.48 mm)
- Paper Feeding: Front/Top Friction Feed,
 Front/Back Push Tractor, Front/Top Pull Tractor
- Standard Tractor: Front/Back Push with Zero Tear, Auto Park and Auto Loading standard

Environmental

• Size (WxDxH):

ML620/ML690 – 17.2" x 14.8" x 7.5" (43.8 cm x 37.5 cm x 19.1 cm) ML621/ML691 – 23.3" x 14.8" x 7.5" (59.2 cm x 37.5 cm x 19.1 cm)

Net Weight:

ML620/ML690 – 16.8 lb. (7.7 kg) ML621/ML691 – 22.0 lb. (10 kg)

Power Consumption:

ML620/ML621 - Operation approx. 52W (ISO/IEC 10561 Letter, Draft, Range 1); Idle 15W max; Sleep Mode - with options 3.7W max, without options 1.5W max

ML690/ML691 – Operation approx. 52W (ISO/IEC 10561 Letter, Roman, Range 1); Idle 15W max; Sleep Mode – with options 3.7W max, without options 1.5W max w

- Electrical: 120V
- Operating Temperature: 5°C to 35°C (41°F to 95°F); 20% to 80% relative humidity
- Noise:

ML620/ML621 – Silent Mode 52.0 dBA, Quiet Mode 55.0 dBA, Normal Mode 57.0 dBA ML690/ML691 – Silent Mode 49.0 dBA, Quiet Mode 52.0 dBA, Normal Mode 57.0 dBA

Reliability and Warranty

- MTBF: 25,000 hours
- Monthly Duty Cycle:
 ML620 28,000 pages; ML621 20,000 pages
 ML690 23,000 pages; ML691 14,000 pages
- Printhead Life: 400 million characters at 25% duty cycle (10 cpi Draft mode)
- Ribbon Life:

ML620/690 – 8 million characters ML621/691 – 13 million characters

• Warranty: 3-Year limited warranty with extensions4

- ² ML620/690 only.
- ³ Depending on paper path and additional tractor used.
- ⁴ Available in the U.S. and Canada only.

All specifications subject to change without notice.

© 2019 Oki Data Americas, Inc. OKI, MICROLINE, OkiLAN Reg. T.M., Oki Electric Industry Co., Ltd. Epson Reg. T.M., Seiko Epson Corp. IBM Reg. T.M., International Business Machines, Inc. Windows, Vista, Reg. T.M., Microsoft Corp. ENERGY STAR Reg. T.M., US EPA.

Ordering Information				
Description	Part Number			
Printers				
ML620 (Dual 9-Pin) – 120V	62433801			
ML621 (Dual 9-Pin) – 120V	62433901			
ML690 (24-Pin) – 120V	62434001			
ML691 (24-Pin) – 120V	62434101			
Accessories				
OkiLAN 7130E 10/100 Base-T Ethernet				
Internal Print Server	45268701			
RS232 Serial Card	44455101			
Cut-Sheet Feeder (ML620/ML6	690) 44497401			
Cut-Sheet Feeder (ML621/ML6	691) 44497501			
Front/Back Push Tractor (ML620/ML690) 44454				
Front/Back Push Tractor (ML621/ML691) 44455001				
Top Pull Tractor (ML620/ML690) 44753901				
Top Pull Tractor (ML621/ML69	91) 44754001			
Roll Paper Stand (ML620/ML6	590 only) 70023301			
Supplies				
Ribbon Cartridge (ML620/ML6	690) 8 MM Char. 44173403			
Ribbon Cartridge (ML621/ML6	691) 13 MM Char. 44173404			
OKIcare® Depot Warranty Enhancement Program				
ML	.620/621 ML690/691			
4-Year Extension 38	38022214 38022614			
5-Year Extension 38022215 38022615				

Note: All Warranty Enhancement Program options extend the <u>total</u> <u>warranty coverage period</u> from the date of purchase to the number of years listed for each order number above.





Oki Data Americas, Inc.

USA

8505 Freeport Pkwy., Suite 600 Irving, TX 75063 Tel: 800.0KI.DATA (800.654.3282) Fax: 856.222.5320

www.oki.com/us

Canada

5800 Hurontario St., Suite 1020 Mississauga, Ontario L5R 4B9 Tel: 905.755.5800 Fax: 905.755.5840

www.oki.com/ca



¹ Super-Speed Draft rated at 12 cpi only; all other print speeds apply to 10 cpi.