# PACEMARK® 3410



# The heavy-duty, high-speed printer for large-volume forms printing.

# **Highlights:**

- Designed for long print runs: data processing, report generation, spreadsheets, etc.
- Tank-Tough® reliability
- Crisp, clear printing even on 8-part forms
- Zero-form tear with auto-form advance
- 8,000-hr. MTBF1
- 550 characters-per-second print speed
- · Rugged design for years of heavy use
- 1-Year On-Site warranty (parts and labor)<sup>2</sup>
- Live, toll-free technical support<sup>2</sup>

PACEMARK® 3410: the dependable, day in/day out, heavy-duty, high-speed printer from OKI®. When your printer is subjected to long runs at high speeds or gets fed a constant stream of multi-part forms and card stock, it had better be a PACEMARK 3410.

OKI designed the PACEMARK 3410 for durable output—with fast throughput and the legendary reliability. The strike force of its printhead carries through an 8-part form with stunning clarity, providing better print quality on any surface.

Three available paper paths make the PACEMARK 3410 more flexible. And, with 64K standard memory, the printer does it all—and does it better.

Performing best in no-nonsense applications calling for heavy duty throughput. For point of sale, the PACEMARK 3410 has the capability of printing to the top edge of the form, and the metal tear bar assures any document on demand.

In back-office applications, its power and speed make light work of the thickest forms.

And, in networked/shared environments, it's an integral part of the whole: parallel and serial interfaces are standard.

Feed it three ways: by the standard bottomfeed or rear-feed push tractors, or single sheets from the top. Short, straight paper paths reduce feeding snags. Quick and easy loading reduces downtime. Feed it anything: continuous forms, multi-part forms, single cut-sheet paper, labels, envelopes, transparencies, even heavy card stock. The PACEMARK 3410 pulls paper through at up to 10 inches per second (ips), and skips spaces at up to 60 ips.

It all comes down to dependability. The PACEMARK® 3410 prints data in a 136-column format using standard characters and in 272 columns at 20 characters per inch. It comes with resident barcode fonts and graphic capabilities, and lets you create personalized characters and symbols with its ASCII 96-character sets plus resident and down-line loadable type fonts.

The PACEMARK 3410 features rugged, built-to-last construction, inside and out. Its 16-bit, 12 MHz control board is an OKI-proprietary CPU that, although designed for simplicity, still processes data faster than its closest competitor.

Fewer parts to wear down or replace, uncomplicated paper paths, and OKI's proven expertise and experience translates into exceptional performance, day in and day out.

For reliability and versatility to count on, the PACEMARK 3410 never rests.

<sup>&</sup>lt;sup>1</sup> 25% duty cycle, 35% page density.

 $<sup>^{\</sup>rm 2}$  Available in the U.S. and Canada only.

# PACEMARK® 3410

# **Specifications**

# **Technology, Speed and Print Characteristics**

- Printhead: 9-Pin SIDM
- Graphics Resolution: 240 (H) x 216 (V) dpi maximum
- Feed Rate: 10 ips
- Print Speed / Character Matrix:

Mode	NLQ	Utility	HS Draft	
Speed (in cps)	105	420	550	
Matrix (H x W)	24 x 17	12 x 9	9 x 9	

#### **Emulation, Interface and Memory**

- Co-resident: Epson® FX-1050; IBM® ProPrinter® III; MICROLINE® and PACEMARK® (optional)
- Interface:
- Standard: Parallel and 19.2K RS-232C
- Standard Memory: 64K

## Compatibility

 Operating Systems: Windows®10, Windows 8.1, Windows 8, Windows 7, Server 2019, Server 2016, Server 2012/R2, Server 2008/R2

#### **Fonts/Characters**

- Code Pages: Standard ASCII; Epson Character Set I & II; IBM Character Set I, II & All Characters; Foreign character substitution; Line graphics; Code page 850 & 863; Bar code (see below)
- NLQ: Courier, Gothic, Proportional
- Draft: Utility, High Speed Draft
- Bar Codes: 8

#### Paper Handling

- Paper Input: Single-part, Multi-part, Continuous forms, Cut sheet, Card stock, Envelopes, Labels
- Number of Copies: Interleaf/Carbonless = 1 + 7;
  Cut sheet = 1
- Thickness: 0.02" (0.5mm)
- Paper Feeding: Top, rear, bottom; Built-in Bottom and Rear Push Tractors, Friction Feed (top), Optional Top Pull Tractor
- Tear Capabilities: Form Tear/Zero tear, Metal tear bar
- Loading: Auto loading for single sheet

### **Warranty and Reliability**

- Limited Warranty: 1-Year On-Site parts, labor and printhead
- MTBF: 8,000 hours (25% duty cycle/35% page density)
- Monthly Workload: 19,000 pages at 25% duty cycle/35% density
- Printhead Life: 200 million characters average in 10 cpi utility mode, 25% duty, 35% page density
- Ribbon Life: 7.5 million characters

#### **Environmental**

- Size (WxDxH): 25.2" x 19" x 15" (incl. Bottom Feed Tractor) (54 cm x 48.3 cm x 20.3 cm)
- Net Weight: 63 lb. (25.4 kg); UPS shippable
- Acoustic Noise: 58 dBA

Ordering Information				
Description		Part Number		
PACEMARK 3410 – 110V		61800801		
Accessories				
Pull Tractor Kit		70011701		
		, 0311, 01		
Ribbons:				
Ribbon Cartridge		52105801		
OKIcare® Warranty Enhancement Programs				
	OKI Depot™	OKI On-Site™		
2-Year Extension	58251511	58255711		
3-Year Extension	58251611	58252611		

Note: All Warranty Enhancement Program options extend the <u>total</u> <u>warranty coverage period</u> from the date of purchase to the number of years listed for each order number above.

1 Available in the U.S. and Canada only.

Specifications are subject to change without notice.

© 2019 Oki Data Americas, Inc. OKI, MICROLINE, OkiLAN, OKIcare Reg. T.M., Oki Electric Industry Co., Ltd. PACEMARK Reg. T.M., Epson Reg.T.M., Seiko Epson Corp. IBM, ProPrinter Reg. T.M., International Business Machines Corp. Windows, VISTA Reg. T.M., Microsoft Corp.

### Oki Data Americas, Inc.

#### USA

8505 Freeport Pkwy., Suite 600 Irving, TX 75063 Tel: 800.0KI.DATA (800.654.3282) Fax: 856.222.5320

www.oki.com/us

## Canada

5800 Hurontario St., Suite 1020 Mississauga, Ontario L5R 4B9 Tel: 905.755.5800 Fax: 905.755.5840

www.oki.com/ca

