Samsung A4 Mono Laser Printer

Pro Xpress

M4530NX I M4530ND





Built for Reliability and Low-Cost Simplicity

Boost print performance with more speed, reliability and storage

Fast, high-volume printing

- Impressive speeds of up to 45 pages per minute (ppm).
- 1 GHz dual-core CPU for more print power and capacity to handle jobs of any size, any complexity.
- 1 GB memory¹ to handle high-volume print jobs.

Reliable performance

- High monthly duty cycle of up to 200,000 sheets handily copes with the demands of high-speed business.
- Anti-jam technology, featuring a friction roller system, reduces multiple sheet pickups and jams to keep workgroups working.

Store more print jobs

- 320 GB standard hard disk drive² provides all the space needed to store more print jobs for pull printing.
- Ample storage means print jobs will be safely stored and ready to pull at a moment's notice.

Sharper-quality print output

- Superior 1,200 x 1,200 effective dpi resolution that delivers crisp, professional-quality output.
- Samsung's Rendering Engine for Clean Page (ReCP) technology for sharp text and clean images.

1 GB standard memory is available on M4530NX model only.

It will be released in major 9 countries (KOR,USA,CAN,GER,UK,ITA,FRA,SWE,NOR) March 30, 2015.

Drive productivity while lowering TCO

High-yield productivity

 Toner cartridges that yield up to 40,000 standard pages, and drums that yield 100,000 standard pages for high productivity and low TCO Separate toner and drum cartridge for fewer replacements.

Instant paper and toner savings

- One Touch Eco Button automatically activates smart printing options to reduce paper and toner usage.
- Duplex, 2-up printing and the option to skip blank pages drive down expenses.

Budget-friendly eco printing

• Samsung Eco Driver reduces toner and paper use by up to 20 percent.

Print easily yet safely on the go with robust document security

Easy, secure touch-to-print usability

- 4.3" touchscreen panel³ for easy print functionality.
- PIN entry using numeric keypad for secure release of print jobs.

Mobilize printing with just a tap

- The Samsung Wireless and Near-Field Communication (NFC) option supports user authentication enables authorized users to tap and print to a printer from mobile devices.
- Using a mobile device, securely release documents held in the printer's memory.

Intuitive cloud-based mobility

- Samsung Cloud Print[™] seamlessly connects mobile devices and printers, allowing users to create, edit and print from anywhere.⁴
- Secure and manage document workflow from start to print while on the go.

Seamless manageability with a secure platform

- XOA Web platform supports ISV productivity solutions without the need for complicated hardware specifications.
- Enhanced security functions safeguard corporate data.



SAMSUNG.
PRINTING INNOVATION.



⁵¹² MB standard memory is available on M4530ND model only.

² 320 GB standard HDD is available on M4530NX model only. Standard HDD is optional for M4530ND model.

 $^{^{\}rm 3}$ Touchscreen panel is available on M4530NX model only.

⁴ SCP(Samsung Cloud Print) 1.0 is available only in Korea.

Samsung A4 Mono Laser Printer **Pro***Xpress* M4530NX I M4530ND

Specifications

			M4530NX	M4530ND	
		Standard	Pr	int	
General	Functions	Value Added	4.3" Touch-Screen LCD / XOA Web	XOA Web	
	Processor		Dual Core 1GHz	(C4N + A1000)	
	Memory	Standard	1 GB	512 MB	
		Max	20		
		Standard	Hi-Speed USB 2.0 Device (1EA), Host (2EA), Ethernet 10/100/1000 Base TX		
	Interface Optional		IEEE 802.11 b/g/n, NFC active		
	Power Consumption		less than 16 W (Ready) / 850 W (Normal operation) / 850 W (Max/Peak) / 1.5W (Sleep) / 0.45 W (Power off) / 2.45 KWh/week (TEC)		
	Noise Level		Less than 54 dBA (Printing) / Less than 30 dBA (Standby)		
	Dimension (WxDxH)		433 x 459.5 x 408.8 mm (17" x 18.1" x 16.1")	433 x 459.5 x 390.7 mm (17" x 18.1" x 15.4")	
	Weight				
	Max. Monthly Duty Cycle		22.0 kg (48.5 lb) 200,000 Pages		
			320 GB N/A		
	Storage	Standard			
		Optional	N/A	320 GB HDD	
	Operational P		4.3" Touch Screen LCD	4 Line LCD	
Print	Speed (Mono)			45 ppm in A4 (47 ppm in Letter)	
	First Print Out Time (Mono)			6.5 sec (From ready)	
	Resolution		Up to 1,200 x 1,200 dpi Effective Output (600 x 600 x 2 bit)		
	Emulation		PCL5e / PCL6 / PostScript3 / PDF Direct V1.7 / XPS / TIFF / URF / PWG		
	Duplex Print		Built-in		
	Client OS Support	Windows	XP (32 / 64bit) / Vista (32 / 64bit) / 2003 Server (32 / 64bit) / 2008 Server (32 / 64bit) / Win7 (32 / 64bit) / 2008 Server R2 (64bit) / Win8.1 (32 / 64bit) / 2012 Server (64bit) / 2012 Server R2 (64bit)		
		Linux	RedHat Enterprise Linux WS 5, 6 / Fedora 12, 13, 14, 15, 16, 17, 18, 19, 20 / openSuSE 11.2, 11.3, 11.4, 12.1, 12.2, 12.3 / Ubuntu 10.04, 10.10, 11.04, 11.10, 12.04, 12.10, 13.04, 13.10, 14.04 / SuSE Linux Enterprise Desktop 10, 11 / Debian 6, 7 / Mint 13, 14, 15, 16		
		UNIX	Sun Solaris 9,10,11 (x86, SPARC) / HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) / IBM AIX 5.1, 5.2, 5.3, 5.4, 6.1, .7.1 (PowerPC)		
		Mac OS	X 10.5 - 10.9		
	Direct Print Support		Yes		
	Print Features		Automatic Double Sided Print / Direct Print / Secure Print		
	Solutions		SyncThru™ Admin / SecuThru™ Lite* / Usage Tracker* (*available May 2015)		
	Standard		550 Sheets Cassette Tray (@75gsm) / (520 Sheets @80gsm)		
	Input Capacity	Multipurpose	100 Sheet MP Tray (@80gsm)		
Paper Handling		Other Options	550 Sheet SCF (@75gsm) x 4		
		Maximum	2,850 Sheet Cassette Tray (550 Std + 100 MP + 4 x 550 SCF)		
	Standard Cassette Tray	Capacity	550 Sheets (@75 gsm)		
		Supuorty	A4 / A5 / A6 / Letter / Legal / Oficio / Folio / JIS B5 / ISO B5 / Executive / Statement / PostCard 4x6 / Envelope Monarch / Envelope No 9 /		
		Media size	Envelope No 10 / Envelope DL / Envelope C6 / Custom		
		Media type	Plain / Thin / Bond / Punched / Pre-Printed / Recycled / Envelope / Label / CardStock / Letterhead / Thick / Cotton / Colored / Archive		
		Media weight	Supported Weight: 60 - 163 g/m² (16 - 43 lb), Thin Paper (60 - 69 g/m²) / Plain Paper (70 - 90 g/m²) / Thick Paper (91 - 120 g/m²) / Bond Paper (105 - 120 g/m²) / Cardstock (121 - 163 g/m²)		
		Capacity	100 Sheets		
	Multipurpose Tray	Media size	Min: 76.2 mm x 127 mm (3"x5") / Max: 216 mm x 356 mm (8.5"x14.0")		
		Media type	Plain / Thin / Bond / Pre-printed / Recycled / Envelope / Label / Cardstock / Thick / Cotton / Colored / Archive / Thicker		
		Media weight	Supported Weight: 60 - 220 g/m² (16 ~ 59 lb), Thin Paper (60 - 69 g/m²) / Plain Paper (70 - 90 g/m²) / Thick Paper (90 - 120 g/m²) / Bond Paper (105 - 120 g/m²) / Cardstock (121 - 163 g/m²) / Thicker Paper (164 - 220 g/m²)		
		Capacity	Bond Paper (105 - 120 g/m-) / Cardstock (121 - 163 g/m-) / Trilicker Paper (164 - 220 g/m-)		
	Other Options	Media size	A4 / A5 / A6 / Letter / Legal / Oficio / Folio / JIS B5 / ISO B5 / Executive / Statement / PostCard 4x6 / Envelope B5 / Envelope Monarch / Envelope C0M-10 / Envelope DL / Envelope C5 / Envelope C6 / Custom		
		Media typo			
		Media type	Plain Paper / Thin Paper / Bond / Punched / Pre-Printed / Recycled / Envelope / Label / CardStock / Letterhead / Thick / Colored / Archive		
	Media weight		Supported Weight: 60 - 163 g/m² (16 - 43 lb), Thin Paper (60 - 70 g/m²) / Plain Paper (70 - 90 g/m²) / Thick Paper (91 - 105 g/m²) / Bond Paper (105 - 120 g/m²) / Cardstock (121 - 163 g/m²)		
Supplies	Output Capacity		500 Sheets Face Down		
	Toner (Black)	Yield	Standard: 7,000 Pages* / High Yield: 20,000 Pages* / Extra High Yield: 40,000 Pages* / *Declared Cartridge Yield in Accordance With ISO/IEC 19752		
		Model Code	MLT-D304S / MLT-D304L / MLT-D304E		
	Drum Unit	Yield	100,000 Pages (* based on simplex 3 average letter/A4-size pages per print job and ~ 5% coverage)		
	Drain Offic	Model Code	MLT-R304		
Option			Second Cassette Tray (SL-SCF4500), Stand (SL-DSK001S), Memory Upgrade Kit (SL-MEM001), Wireless LAN (SL-NWE001X (Wireless + NFC))	Second Cassette Tray (SL-SCF4500), Stand (SL-DSK001S), Memory Upgrade Kit (SL-MEM001), Wireless LAN (SL-NWE001X (Wireless + HDD Kit (SL-HDK4001)	



Copyright © 2014 Samsung Electronics Co., Ltd. All rights reserved. Samsung, Business Core, SecuThru, and SmarThru are either trademarks or registered trademarks of Samsung Electronics Co., Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged. Windows, XP and Vista are registered trademarks of Microsoft Corporation. The registered trademark Linux® is used pursuant to a sublicense from LMI, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis. Ubuntu is a registered trademark of Canonical Ltd. SuSE Linux is a registered trademark of SUSE LLC in the United States and other countries. Defiant is a registered trademark owned by Software in the Public Interest, Inc., Linux Mirt is a trademark of Canonical, Inc. UNIX is a trademark of The Open Group. Sun Solaris is a trademark of Hewlett Packard Company. PA-RISC is a trademark of Hewlett-Packard. Itanium is a trademark or registered trademark of Intel Corporation or its subsidiaries in the United States and other countries. BM AIX and PowerPC are trademarks of International Business Machines Corporation. Mac OS X is a trademark of Apple Inc., registered in the U.S. and other countries.







